



Visit : python.mykvs.in for regular updates

Dictionary

It is an unordered collection of items where each item consist of a key and a value.
It is mutable (can modify its contents) but Key must be unique and immutable.



`{'key': 'value'}`

Dictionary

Creating A Dictionary

It is enclosed in curly braces {} and each item is separated from other item by a comma(,). Within each item, key and value are separated by a colon (:). Passing value in dictionary at declaration is dictionary initialization.get() method is used to access value of a key

e.g.

```
dict = {'Subject': 'Informatic Practices', 'Class': '11'}
```

Accessing List Item

```
dict = {'Subject': 'Informatics Practices', 'Class': 11}
```

```
print(dict)
```

```
print ("Subject : ", dict['Subject'])
```

```
print ("Class : ", dict.get('Class'))
```

OUTPUT

```
{'Class': '11', 'Subject': 'Informatics Practices'}
```

```
('Subject : ', 'Informatics Practices')
```

```
('Class : ', 11)
```

Dictionary

Iterating / Traversing through A Dictionary

Following example will show how dictionary items can be accessed through loop.

e.g.

```
dict = {'Subject': 'Informatics Practices', 'Class': 11}
```

```
for i in dict:
```

```
    print(dict[i])
```

OUTPUT

11

Informatics Practices

Updating/Manipulating Dictionary Elements

We can change the individual element of dictionary.

e.g.

```
dict = {'Subject': 'Informatics Practices', 'Class': 11}
```

```
dict['Subject']='computer science'
```

```
print(dict)
```

OUTPUT

```
{'Class': 11, 'Subject': 'computer science'}
```

Deleting Dictionary Elements

del, pop() and clear() statement are used to remove elements from the dictionary.

del e.g.

```
dict = {'Subject': 'Informatics Practices', 'Class': 11}
print('before del', dict)
del dict['Class'] # delete single element
print('after item delete', dict)
del dict #delete whole dictionary
print('after dictionary delete', dict)
```

Output

```
('before del', {'Class': 11, 'Subject': 'Informatics Practices'})
('after item delete', {'Subject': 'Informatics Practices'})
('after dictionary delete', <type 'dict'>)
```

pop() method is used to remove a particular item in a dictionary. clear() method is used to remove all elements from the dictionary.

e.g.

```
dict = {'Subject': 'Informatics Practices', 'Class': 11}
print('before del', dict)
dict.pop('Class')
print('after item delete', dict)
dict.clear()
print('after clear', dict)
```

Output

```
('before del', {'Class': 11, 'Subject': 'Informatics Practices'})
('after item delete', {'Subject': 'Informatics Practices'})
('after clear', {})
```

Built-in Dictionary Functions

S.No.	Function & Description
1	<u>len(dict)</u> Gives the total length of the dictionary. It is equal to the number of items in the dictionary. <code>dict = {'Name': 'Aman', 'Age': 37}; print ("Length : %d" % len (dict))</code> OUTPUT ->2
2	<u>str(dict)</u> Return a printable string representation of a dictionary
3	<u>type(variable)</u> If variable is dictionary, then it would return a dictionary type.

Built-in Dictionary Methods

S.No.	Method & Description
1	<code>dict()</code> - creates dictionary <code>x = dict(name = "Aman", age = 37, country = "India")</code> Here x is created as dictionary
2	<code>keys()</code> - returns all the available keys <code>x = dict(name = "Aman", age = 37, country = "India")</code> <code>print(x.keys())</code> OUTPUT-> <code>dict_keys(['country', 'age', 'name'])</code>
3	<code>values()</code> - returns all the available values <code>x = dict(name = "Aman", age = 37, country = "India")</code> <code>print(x.values())</code> OUTPUT-> <code>dict_values(['India', 37, 'Aman'])</code>

Built-in Dictionary Methods

S.No.	Method & Description
4	<p><code>items()</code> - return the list with all dictionary keys with values.</p> <pre>x = dict(name = "Aman", age = 37, country = "India") print(x.items()) OUTPUT->dict_items([('country', 'India'), ('age', 37), ('name', 'Aman')])</pre>
5	<p><code>update()</code>-used to change the values of a key and add new keys</p> <pre>x = dict(name = "Aman", age = 37, country = "India") d1 = dict(age= 39) x.update(d1,state="Rajasthan") print(x) OUTPUT-{'country': 'India', 'age': 39,'name':'Aman','state': 'Rajasthan'}</pre>

Built-in Dictionary Methods

S.No.	Method & Description
6	<p><code>del</code> -used to remove key <code>x = dict(name = "Aman", age = 37, country = "India")</code> <code>del x['age']</code> <code>print(x)</code> OUTPUT->{'country': 'India', 'name': 'Aman'} <code>del x</code> -> will remove complete dictionary</p>
7	<p><code>fromkeys()</code> – is used to create dictionary from keys <code>keys = {'a', 'e', 'i', 'o', 'u' }</code> <code>value = "Vowel"</code> <code>vowels = dict.fromkeys(keys, value)</code> <code>print(vowels)</code> OUTPUT-> {'i': 'Vowel', 'u': 'Vowel', 'e': 'Vowel', 'a': 'Vowel', 'o': 'Vowel'}</p>

Built-in Dictionary Methods

S.No.	Method & Description
8	<p><code>copy()</code> - returns a shallow copy of the dictionary.</p> <pre>x = dict(name = "Aman", age = 37, country = "India") y=x.copy() print(y) print(id(x)) print(id(y))</pre> <p>OUTPUT - >{'country': 'India', 'age': 37, 'name': 'Aman'}</p> <p>33047872</p> <p>33047440</p>
9	<p><code>popitem()</code> – removes last item from dictionary</p> <pre>x = dict(name = "Aman", age = 37, country = "India") x.popitem() print(x)</pre> <p>OUTPUT-> {'age': 37, 'name': 'Aman'}</p>

Built-in Dictionary Methods

S.No.	Method & Description
10	<p><code>setdefault()</code> method returns the value of the item with the specified key. If the key does not exist, insert the key, with the specified value.</p> <pre>x = dict(name = "Aman", country = "India") y=x.setdefault('age',39) print(y) OUTPUT-> 39</pre>
11	<p><code>max()</code> – returns key having maximum value T_v = {'a':100, 'b':1292, 'c' : 88}</p> <pre>Keymax = max(Tv, key=Tv.get) print(Keymax) OUTPUT-> b</pre>
12	<p><code>min()</code>- returns key having minimum value</p>

Built-in Dictionary Methods

S.No.	Method & Description
13	sorted- sort by key or value dict1 = {'b':100, 'a':12, 'c' : 88} y = sorted(dict1.items(),key=lambda x: x[1],reverse=True) print(y) OUTPUT-> [('b', 100), ('c', 88), ('a', 12)]

count the number of times a character appears in a given string using a dictionary

```
input_string = "python.mykvs.in"  
frequencies = {}  
for char in input_string:  
    if char in frequencies:  
        frequencies[char] += 1  
    else:  
        frequencies[char] = 1  
print ("Per char frequency in '{}' is :\n{}".format(input_string, str(frequencies)))
```

OUTPUT

Per char frequency in 'python.mykvs.in' is :

{'i': 1, 'h': 1, 'k': 1, 'm': 1, 'o': 1, 'n': 2, 'p': 1, 's': 1, 't': 1, 'v': 1, 'y': 2, '.': 2}

**create a dictionary with names of employees,
their salary and access them**

employees =

{'Aman':{'salary':'10000'},'Mayur':{'salary':'51000'}}}

employee1 = employees['Aman']

print(employee1)

OUTPUT

{'salary': '10000'}

Questions.

1. Create dictionary to store 4 student details with rollno,name,age field. Search student in list.
2. Create dictionary for month and noofdays for a year. User is asked to enter month name and system will show no of days of that month.